Form Approved. OMB No. 2040-0086

Approval expires 5-31-92

Please print or type in the unshaded areas only

Form 2F NPDES

I Outfall I coation



United States Environmental Protection Agency Washington, DC 20460

Application for Permit to Discharge Storm Water Discharges Associated with Industrial Activity

Paperwork Reduction Act Notice

Public reporting burden for this application is estimated to average 28.6 hours per application, including time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding the burden estimate, any other aspect of this collection of information, or suggestions for improving this form, including suggestions which may increase or reduce this burden to: Chief, Information Policy Branch, PM-223, U.S. Environmental Protection Agency, 401 M St., SW, Washington, DC 20460, or Director, Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503 20503.

For each outfall, list the lat	itude and l	onaitude (of its locat	ion to the	nearest 15	seconds a	and the name of the receiving water.		
A. Outfall Number]			D. Receiving Water		
(list)		B. Latitude	•	C. Longitude		le	(name)		i
1							~		-
				1					
II. improvements		,							
A. Are you now required operation of wastewat in this application? The schedule letters, stipul	er treatme nis include	ent equipm es. but is r	nent or pra not limited	actices or a l to, permi	any other e it condition	t any impl nvironme ns, admini	lementation schedule for the construction ntal programs which may affect the disclistrative or enforcement orders, enforcer	on, upgrad narges des nent comp	ding or scribed oliance
-,								4. F	inal
 Identification of Condi 	tions,	2. Affected Outfalls						Complia	nce Date
Agreements, Etc.		number-	sour	ce of disc	harge		3. Brief Description of Project	a. req.	b. proj.
						5.7			
			·						
					,				
							Y		
:-									
						·			
				1.		1,000			
							or other environmental projects which	******	•

discharges) you now have under way or which you plan. Indicate whether each program is now under way or planned, and indicate your actual or planned schedules for construction.

III. Site Drainage Map

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfall(s) covered in the application if a topographic map is unavailable) depicting the facility including: each of its intake and discharge structures; the drainage area of each storm water outfall; paved areas and buildings within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage or disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used to accumulating hazardous waste under 40 CFR 262.34); each well where fluids from the facility are injected underground; springs, and other surface water bodies which receive storm water discharges from the facility.

Outfall	r each outfall, provide an estimate outfall, and an estimate of the tot Area of Impervious Surface	al surface area drained by t	he outfail.			
Number	(provide units)	(provide units)	Number	Area of Impervious Surface (provide units)		Area Drained ovide units)
en	ovide a narrative description of sig anner to allow exposure to storm aployed to minimize contact by the diffequency in which pesticides, he	water; method of treatme	nt, storage, o vater runoff: r	r disposal; past and present ma naterials loading and access are	tariala mana	mamani mendin
SIU	r each outfall, provide the location rm water runoff; and a description d treatment measures and the ultin	i of the freatment the storn	n water receiv	ee including the echedule and t	asures to red ope of mainte	uce pollutants nance for cont
Outfall						List Codes fr
lumber		Treatn	nent	· · · · · · · · · · · · · · · · · · ·	, , , <u>, , , , , , , , , , , , , , , , </u>	Table 2F-
V. Non	stormwater Discharges					
A. I ce dis	ertify under penalty of law that the charges, and that all nonstormwa plication for the outfall	outfall(s) covered by this a ater discharges from these	pplication have outfall(s) are	ve been tested or evaluated for the identified in either an accomp	ne presence o anying Form	of nonstormwat 2C or Form 2
lame and	Official Title (type or print)	Signature		, 1944ddin, 19	Date Sign	ed
B. Pro	vide a description of the method u	sed, the date of any testing	, and the onsi	te drainage points that were dire	ctly observed	during a test.
			-			

EPA Form 3510-2F (Rev. 1-92)

EPA ID Number (copy from Item I of Form 1)

Continued from Page 2

VII. Discharge Inform	nation				
A,B,C, & D: See instruction	ns before proceeding. C	complete one set of tables for ea		utfall number ir	the space provided.
E: Potential discharges not	ot covered by analysis - is	ded on separate sheets number s any toxic pollutant listed in tab intermediate or final product or b	ole 2F-2, 2F-3 or 2F-4, a su	ubstance or a c	omponant of a substance
· ·	h pollutants below)		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	No (go	to Section IX)
e e e e e e e e e e e e e e e e e e e					
					,
Total Taylo	To Treatmen Date	. *			
VIII. Biological Toxic Do you have any knowledg	ge or reason to believe to	that any biological test for acute	or chronic toxicity has be	een made on a	ny of your discharges or
on a receiving water in rela	ation to your discharge w	rithin the last 3 years?			
Yes (list all such	h pollutants below)		i .	No (go	to Section IX)
				:	
IX. Contract Analysis					
		ormed by a contract laboratory of	or consulting firm?		•
Yes (list the nationalized by	me, address, and telep	phone number of, and pollutan	ts	No (go	to Section X)
A. Nam		B. Address	C. Area Code &	Phone No.	D. Pollutants Analyzed
			1		
	:				3
~	.				
X. Certification					
I certify under per supervision in acco the information sub directly responsible belief, true, accurat	ordance with a systomitted. Based on model of the for gathering the steel and complete. I	this document and all a tem designed to assure to my inquiry of the person o information, the informat am aware that there are prisonment for knowing vi	hat qualified personn or persons who mana tion submitted is, to significant penalties i	el properly ge the syste the best of	gather and evaluate m or those persons mv knowledge and
A. Name & Official Title (ty)	pe or print)			B. Area Cod	e and Phone No.
C. Signature				D. Date Sign	ned

Form Approved. OMB No. 2040-0086

						Approval expires 5-31-93
	The state of the s	ontinued from pa		45.50		
Part A - You r						lete one table for each outfall. See
		ım Values	1	e Values	Number	
Pollutant		de units)		de units)	of	e de la companya de l
and	Grab Sample Taken During		Grab Sample Taken During		Storm	
CAS Number	First 20	Flow-weighted	First 20	Flow-weighted	Events	
(if available)	Minutes	Composite	Minutes	Composite	Sampled	Sources of Pollutants
Oil and Grease		N/A				
Biological Oxygen						
Demand (BOD5)						
Chemical Oxygen						
Demand (COD)						
Total Suspended						
Solids (TSS)						
Total	. ***.			rayera e		
Nitrogen			1			
Total					į	
Phosp horus					İ	
рН	Minimum	Maximum	Minimum	Maximum		
Part B - List ea	ach pollutant that is	limited in an effluer	nt guideline which th	ne facility is subject	to or any p	ollutant listed in the facility's NPDES mplete one table for each outfall. See
the ins	structions for addition	nal details and requ	y is operating under i irements.	an existing NPDES	permit). Cor	mplete one table for each outfall. See
		ım Values		e Values	Number	
Pollutant (include units)		(includ	le units)	of		
and	Grab Sample		Grab Sample		Storm	
CAS Number	Taken During First 20	Flow-weighted	Taken During First 20	Flow-weighted	Events	
(if available)	Minutes	Composite	Minutes	Composite	Sampled	Sources of Pollutants
						N-10-10-10-10-10-10-10-10-10-10-10-10-10-
				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1	
					1	
					1	TOTAL CONTRACTOR OF THE CONTRA
					 	
				 	 	
					†	
7						
					 	And the second s
					1	
					1	14
					1	
		<u> </u>			 	
				 	1	
				<u> </u>	1	
		-				
		1	1		<u> </u>	

^ •		1		t	F
Cont	เทนเ	aa tr	om t	ne	Front

Part C	- List ea additi	ach polluta onal details	nt shown and requ	in Tables 2F-2, 2F-3 irements. Complete	, and 2F-4 that you lone table for each o	know or hautfall.	ave reaso	n to believ	e is preser	nt. See the instructions for
Pollu			Maximun (include	n Values	Average (include	Values		Number of		·
an CAS No	nd umber	Grab S Taken I First	ample During t 20	Flow-weighted	Grab Sample Taken During First 20 Minutes	Flow-we		Storm Events	c	Second Dallistanta
(if avai	ilabiej	Minu	ites	Composite	Minutes	Comp	XOSILE	Sampled		Sources of Pollutants
	-		4.	1 1						
		 		· · · · · · · · · · · · · · · · · · ·					<u> </u>	
						1.				
					-					
		<u> </u>								
	:		$\overline{}$			<u> </u>				
		<u> </u>								
		<u> </u>				 			· · · · · · · · · · · · · · · · · · ·	
				- 7 - 12 - 1, 1 - 1		-				
			•							
		<u> </u>								
		<u> </u>		<u> </u>		'		 	<u> </u>	
		 		 						<u> </u>
		<u> </u>		<u> </u>		<u> </u>		1	 	
		 		<u> </u>				 		
										· · ·
									-	
		<u>l</u>		1		<u> </u>	- 4	1 11 11 1	<u> </u>	
Part D		de data for 2.	the storm	event(s) which result 3.	ted in the maximum 4.	values for	the flow w	veighted co 5.	mposite s	ample. 6.
Date of	1	ation	į 7	o. Total rainfall	Number of hours t	between	Maximu	um flow rate	e during	Total flow from
Storm	of Stor	rm Event	durii	ng storm event	beginning of storr ured and end of p measurable rain	n meas- revious		rain event	- 1	rain event
Event	(in mi	inutes)		(in inches)	measurable rain	event		llons/minu specify uni	ts	(gallons or specify units)
			l			!				
	;		ĺ							
				* .		I				
		ļ	l							
			i							
! !	1		ŀ							
	<u> </u>		l			· .				
7. Pr	ovide a de	escription o	of the met	hod of flow measure	ment or estimate.					
J										
į										·

Instructions - Form 2F Application for Permit to Discharge Storm Water Associated with Industrial Activity

Who Must File Form 2F

Form 2F must be completed by operators of facilities which discharge storm water associated with industrial activity or by operators of storm water discharges that EPA is evaluating for designation as a significant contributor of pollutants to waters of the United States, or as contributing to a violation of a water quality standard.

Operators of discharges which are composed entirely of storm water must complete Form 2F (EPA Form 3510-2F) in conjunction with Form 1 (EPA Form 3510-1).

Operators of discharges of storm water which are combined with process wastewater (process wastewater is water that comes into direct contact with or results from the production or use of any raw material, intermediate product, finished product, byproduct, waste product, or wastewater) must complete and submit Form 2F, Form 1, and Form 2C (EPA Form 3510-2C).

Operators of discharges of storm water which are combined with nonprocess wastewater (nonprocess wastewater includes noncontact cooling water and sanitary wastes which are not regulated by effluent guidelines or a new source performance standard, except discharges by educational, medical, or commercial chemical laboratories) must complete Form 1, Form 2F, and Form 2E (EPA Form 3510-2E).

Operators of new sources or new discharges of storm water associated with industrial activity which will be combined with other nonstormwater new sources or new discharges must submit Form 1, Form 2F, and Form 2D (EPA Form 3510-2D).

Where to File Applications

The application forms should be sent to the EPA Regional Office which covers the State in which the facility is located. Form 2F must be used only when applying for permits in States where the NPDES permits program is administered by EPA. For facilities located in States which are approved to administer the NPDES permits program, the State environmental agency should be contacted for proper permit application forms and instructions.

Information on whether a particular program is administered by EPA or by a State agency can be obtained from your EPA Regional Office. Form 1, Table 1 of the "General Instructions" lists the addresses of EPA Regional Offices and the States within the jurisdiction of each Office.

Completeness

Your application will not be considered complete unless you answer every question on this form and on Form 1. If an item does not apply to you, enter "NA" (for not applicable) to show that you considered the question.

Public Availability of Submitted Information

You may not claim as confidential any information required by this form or Form 1, whether the information is reported on the forms or in an attachment. Section 402(j) of the Clean Water Act requires that all permit applications will be available to the public. This information will be made available to the public upon request.

Any information you submit to EPA which goes beyond that required by this form, Form 1, or Form 2C you may claim as confidential, but claims for information which are effluent data will be denied.

If you do not assert a claim of confidentiality at the time of submitting the information, EPA may make the information public without further notice to you. Claims of confidentiality will be handled in accordance with EPA's business confidentiality regulations at 40 CFR Part 2.

Definitions

All significant terms used in these instructions and in the form are defined in the glossary found in the General Instructions which accompany Form 1.

EPA ID Number

Fill in your EPA Identification Number at the top of each odd-numbered page of Form 2F. You may copy this number directly from item I of Form 1.

Item I

You may use the map you provided for item XI of Form 1 to determine the latitude and longitude of each of your outfalls and the name of the receiving water.

Item II-A

If you check "yes" to this question, complete all parts of the chart, or attach a copy of any previous submission you have made to EPA containing the same information.

Item II-B

You are not required to submit a description of future pollution control projects if you do not wish to or if none is planned.

Item III

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfall(s) covered in the application if a topographic map is unavailable) depicting the facility including:

each of its drainage and discharge structures;

the drainage area of each storm water outfall;

paved areas and building within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage or disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied;

each of its hazardous waste treatment, storage or disposal facilities (including each area not required to have a RCRA permit which is used for accumulating hazardous waste for less than 90 days under 40 CFR 262.34);

each well where fluids from the facility are injected underground; and

springs, and other surface water bodies which receive storm water discharges from the facility;

Item IV-A

For each outfall, provide an estimate of the area drained by the outfall which is covered by impervious surfaces. For the purpose of this application, impervious surfaces are surfaces where storm water runs off at rates that are significantly higher than background rates (e.g., predevelopment levels) and include paved areas, building roofs, parking lots, and roadways. Include an estimate of the total area (including all impervious and pervious areas) drained by each outfall. The site map required under item III can be used to estimate the total area drained by each outfall.

Item IV-B

Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored, or disposed in a manner to allow exposure to storm water; method of treatment, storage or disposal of these materials; past and present materials management practices employed, in the last three years, to minimize contact by these materials with storm water runoff; materials loading and access areas; and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied. Significant materials should be identified by chemical name, form (e.g., powder, liquid, etc.), and type of container or treatment unit. Indicate any materials treated, stored, or disposed of together. "Significant materials" includes, but is not limited to: raw materials; fuels; materials such as solvents, detergents, and plastic pellets; finished materials such as metallic products; raw materials used in food processing or production; hazardous substances designated under Section 101(14) of CERCLA; any chemical the facility is required to report pursuant to Section 313 of Title III of SARA; fertilizers; pesticides; and waste products such as ashes, slag and sludge that have the potential to be released with storm water discharges.

Item IV-C

For each outfall, structural controls include structures which enclose material handling or storage areas, covering materials, berms, dikes, or diversion ditches around manufacturing, production, storage or treatment units, retention ponds, etc. Nonstructural controls include practices such as spill prevention plans, employee training, visual inspections, preventive maintenance, and housekeeping measures that are used to prevent or minimize the potential for releases of pollutants.

Item V

Provide a certification that all outfalls that should contain storm water discharges associated with industrial activity have been tested or evaluated for the presence of non-storm water discharges which are not covered by an NPDES permit. Tests for such non-storm water discharges may include smoke tests, fluorometric dye tests, analysis of accurate schematics, as well as other appropriate tests. Part B must include a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test. All non-storm water discharges must be identified in a Form 2C or Form 2E which must accompany this application (see beginning of instructions under section titled "Who Must File Form 2F" for a description of when Form 2C and Form 2E must be submitted).

Item VI

Provide a description of existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years.

Item VII-A, B, and C

These items require you to collect and report data on the pollutants discharged for each of your outfalls. Each part of this item addresses a different set of pollutants and must be completed in accordance with the specific instructions for that part. The following general instructions apply to the entire item.

General Instructions

Part A requires you to report at least one analysis for each pollutant listed. Parts B and C require you to report analytical data in two ways. For some pollutants addressed in Parts B and C, if you know or have reason to know that the pollutant is present in your discharge, you may be required to list the pollutant and test (sample and analyze) and report the levels of the pollutants in your discharge. For all other pollutants addressed in Parts B and C, you must list the pollutant if you know or have reason to know that the pollutant is present in the discharge, and either report quantitative data for the pollutant or briefly describe the reasons the pollutant is expected to be discharged. (See specific instructions on the form and below for Parts A through C.) Base your determination that a pollutant is present in or absent from your discharge on your knowledge of your raw materials, material management practices, maintenance chemicals, history of spills and releases, intermediate and final products and byproducts, and any previous analyses known to you of your effluent or similar effluent.

A. Sampling: The collection of the samples for the reported analyses should be supervised by a person experienced in performing sampling of industrial wastewater or storm water discharges. You may contact EPA or your State permitting authority for detailed guidance on sampling techniques and for answers to specific questions. Any specific requirements contained in the applicable analytical methods should be followed for sample containers, sample preservation, holding times, the collection of duplicate samples, etc. The time when you sample should be representative, to the extent feasible, of your treatment system operating properly with no system upsets. Samples should be collected from the center of the flow channel, where turbulence is at a maximum, at a site specified in your present permit, or at any site adequate for the collection of a representative sample.

For pH, temperature, cyanide, total phenols, residual chlorine, oil and grease, and fecal coliform, grab samples taken during the first 30 minutes (or as soon thereafter as practicable) of the discharge must be used (you are not required to analyze a flow-weighted composite for these parameters). For all other pollutants both a grab sample collected during the first 30 minutes (or as soon thereafter as practicable) of the discharge and a flow-weighted composite sample must be analyzed. However, a minimum of one grab sample may be taken for effluents from holding ponds or other impoundments with a retention period of greater than 24 hours.

All samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches and at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where feasible, the variance in the duration of the event and the total rainfall of the event should not exceed 50 percent from the average or median rainfall event in that area.

A grab sample shall be taken during the first thirty minutes of the discharge (or as soon thereafter as practicable), and a flow-weighted composite shall be taken for the entire event or for the first three hours of the event.

Grab and composite samples are defined as follows:

Grab sample: An individual sample of at least 100 milliliters collected during the first thirty minutes (or as soon thereafter as practicable) of the discharge. This sample is to be analyzed separately from the composite sample.

Flow-Weighted Composite sample: A flow-weighted composite sample may be taken with a continuous sampler that proportions the amount of sample collected with the flow rate or as a combination of a minimum of three sample aliquots taken in each hour of discharge for the entire event or for the first three hours of the event, with each aliquot being at least 100 milliliters and collected with a minimum period of fifteen minutes between aliquot collections. The composite must be flow proportional; either the time interval between each aliquot or the volume of each aliquot must be proportional to either the stream flow at the time of sampling or the total stream flow since the collection of the previous aliquot. Aliquots may be collected manually or automatically. Where GC/MS Volatile Organic Analysis (VOA) is required, aliquots must be combined in the laboratory immediately before analysis. Only one analysis for the composite sample is required.

Data from samples taken in the past may be used, provided that:

All data requirements are met;

Sampling was done no more than three years before submission; and

All data are representative of the present discharge.

Among the factors which would cause the data to be unrepresentative are significant changes in production level, changes in raw materials, processes, or final products, and changes in storm water treatment. When the Agency promulgates new analytical methods in 40 CFR Part 136, EPA will provide information as to when you should use the new methods to generate data on your discharges. Of course, the Director may request additional information, including current quantitative data, if they determine it to be necessary to assess your discharges. The Director may allow or establish appropriate site-specific sampling procedures or requirements, including sampling locations, the season in which the sampling takes place, the minimum duration between the previous measurable storm event and the storm event sampled, the minimum or maximum level of precipitation required for an appropriate storm event, the form of precipitation sampled (snow melt or rainfall), protocols for collecting samples under 40 CFR Part 136, and additional time for submitting data on a case-by-case basis.

B. Reporting: All levels must be reported as concentration and mass (note: grab samples are reported in terms of concentration). You may report some or all of the required data by attaching separate sheets of paper instead of filling out pages VII-1 and VII-2 if the separate sheets contain all the required information in a format which is constant with pages VII-1 and VII-2 in spacing and identification of pollutants and columns. Use the following abbreviations in the columns headed "Units."

	Concentration		Mass
ppm	parts per million	lbs	pounds
mg/1	milligrams per liter	ton	tons (English tons)
ppb	parts per billion	mg	milligrams
ug/1	micrograms per liter	g	grams
kg	kilograms	T	tonnes (metric tons)

All reporting of values for metals must be in terms of "total recoverable metal," unless:

- (1) An applicable, promulgated effluent limitation or standard specifies the limitation for the metal in dissolved, valent, or total form; or
- (2) All approved analytical methods for the metal inherently measure only its dissolved form (e.g., hexavalent chromium); or
- (3) The permitting authority has determined that in establishing case-by-case limitations it is necessary to express the limitations on the metal in dissolved, valent, or total form to carry out the provisions of the CWA. If you measure only one grab sample and one flow-weighted composite sample for a given outfall, complete only the "Maximum Values" columns and insert "1" into the "Number of Storm Events Sampled" column. The permitting authority may require you to conduct additional analyses to further characterize your discharges.

If you measure more than one value for a grab sample or a flow-weighted composite sample for a given outfall and those values are representative of your discharge, you must report them. You must describe your method of testing and data analysis. You also must determine the average of all values within the last year and report the concentration and mass under the "Average Values" columns, and the total number of storm events sampled under the "Number of Storm Events Sampled" columns.

C. Analysis: You must use test methods promulgated in 40 CFR Part 136; however, if none has been promulgated for a particular pollutant, you may use any suitable method for measuring the level of the pollutant in your discharge provided that you submit a description of the method or a reference to a published method. Your description should include the sample holding time, preservation techniques, and the quality control measures which you used. If you have two or more substantially identical outfalls, you may request permission from your permitting authority to sample and analyze only one outfall and submit the results of the analysis for other substantially identical outfalls. If your request is granted by the permitting authority, on a separate sheet attached to the application form, identify which outfall you did test, and describe why the outfalls which you did not test are substantially identical to the outfall which you did test.

Part VII-A

Part VII-A must be completed by all applicants for all outfalls who must complete Form 2F.

Analyze a grab sample collected during the first thirty minutes (or as soon thereafter as practicable) of the discharge and flow-weighted composite samples for all pollutants in this Part, and report the results except use only grab samples for pH and oil and grease. See discussion in General Instructions to Item VII for definitions of grab sample collected during the first thirty minutes of discharge and flow-weighted composite sample. The "Average Values" column is not compulsory but should be filled out if data are available.

Part VII-B

List all pollutants that are limited in an effluent guideline which the facility is subject to (see 40 CFR Subchapter N to determine which pollutants are limited in effluent guidelines) or any pollutant listed in the facility's NPDES permit for its process wastewater (if the facility is operating under an existing NPDES permit). Complete one table for each outfall. See discussion in General instructions to item VII for definitions of grab sample collected during the first thirty minutes (or as soon thereafter as practicable) of discharge and flowweighted composite sample. The "Average Values" column is not compulsory but should be filled out if data are available.

Analyze a grab sample collected during the first thirty minutes of the discharge and flow-weighted composite samples for all pollutants in this Part, and report the results, except as provided in the General Instructions.

Part VII-C

Part VII-C must be completed by all applicants for all outfalls which discharge storm water associated with industrial activity, or that EPA is evaluating for designation as a significant contributor of pollutants to waters of the United States, or as contributing to a violation of a water quality standard. Use both a grab sample and a composite sample for all pollutants you analyze for in this part except use grab samples for residual chlorine and fecal coliform. The "Average Values" column is not compulsory but should be filled out if data are available. Part C requires you to address the pollutants in Table 2F-2, 2F-3, and 2F-4 for each outfall. Pollutants in each of these Tables are addressed differently.

Table 2F-2: For each outfall, list all pollutants in Table 2F-2 that you know or have reason to believe are discharged (except pollutants previously listed in Part VII-B). If a pollutant is limited in an effluent guideline limitation which the facility is subject to, the pollutant must be analyzed and reported in Part VII-B. If a pollutant in Table 2F-2 is indirectly limited by an effluent guideline limitation through an indicator (e.g., use of TSS as an indicator to control the discharge of iron and aluminum), you must analyze for it and report the data in Part VII-B. For other pollutants listed in Table 2F-2 (those not limited directly or indirectly by an effluent limitation guideline), that you know or have reason to believe are discharged, you must either report quantitative data or briefly describe the reasons the pollutant is expected to be discharged.

Table 2F-3: For each outfall, list all pollutants in Table 2F-3 that you know or have reason to believe are discharged. For every pollutant in Table 2F-3 expected to be discharged in concentrations of 10 ppb or greater, you must submit quantitative data. For acrolein, acrylonitrile, 2,4 dinitrophenol, and 2-methyl-4,6 dinitrophenol, you must submit quantitative data if any of these four pollutants is expected to be discharged

in concentrations of 100 ppb or greater. For every pollutant expected to be discharged in concentrations less than 10 ppb (or 100 ppb for the four pollutants listed above), then you must either submit quantitative data or briefly describe the reasons the pollutant is expected to be discharged.

Small Business Exemption - If you are a "small business," you are exempt from the reporting requirements for the organic toxic pollutants listed in Table 2F-3. There are two ways in which you can qualify as a "small business". If your facility is a coal mine, and if your probable total annual production is less than 100,000 tons per year, you may submit past production data or estimated future production (such as a schedule of estimated total production under 30 CFR 795.14(c)) instead of conducting analyses for the organic toxic pollutants. If your facility is not a coal mine, and if your gross total annual sales for the most recent three years average less than \$100,000 per year (in second quarter 1980 dollars), you may submit sales data for those years instead of conducting analyses for the organic toxic pollutants. The production or sales data must be for the facility which is the source of the discharge. The data should not be limited to production or sales for the process or processes which contribute to the discharge, unless those are the only processes at your facility. For sales data, in situations involving intracorporate transfer of goods and services, the transfer price per unit should approximate market prices for those goods and services as closely as possible. Sales figures for years after 1980 should be indexed to the second quarter of 1980 by using the gross national product price deflator (second quarter of 1980 = 100). This index is available in National Income and Product Accounts of the United States (Department of Commerce, Bureau of Economic Analysis).

Table 2F-4: For each outfall, list any pollutant in Table 2F-4 that you know or believe to be present in the discharge and explain why you believe it to be present. No analysis is required, but if you have analytical data, you must report them. Note: Under 40 CFR 117.12(a)(2), certain discharges of hazardous substances (listed at 40 CFR 177.21 or 40 CFR 302.4) may be exempted from the requirements of section 311 of CWA, which establishes reporting requirements, civil penalties, and liability for cleanup costs for spills of oil and hazardous substances. A discharge of a particular substance may be exempted if the origin, source, and amount of the discharged substances are identified in the NPDES permit application or in the permit, if the permit contains a requirement for treatment of the discharge, and if the treatment is in place. To apply for an exclusion of the discharge of any hazardous substance from the requirements of section 311, attach additional sheets of paper to your form, setting forth the following information:

- 1. The substance and the amount of each substance which may be discharged.
- 2. The origin and source of the discharge of the substance.
- 3. The treatment which is to be provided for the discharge by:
 - a. An onsite treatment system separate from any treatment system treating your normal discharge;
 - A treatment system designed to treat your normal discharge and which is additionally capable
 of treating the amount of the substance identified under paragraph 1 above; or
 - c. Any combination of the above.

See 40 CFR 117.12(a)(2) and (c), published on August 29, 1979, in 44 FR 50766, or contact your Regional Office (Table 1 on Form 1, Instructions), for further information on exclusions from section 311.

Part VII-D

If sampling is conducted during more than one storm event, you only need to report the information requested in Part VII-D for the storm event(s) which resulted in any maximum pollutant concentration reported in Part VII-B, or VII-C.

Provide flow measurements or estimates of the flow rate, and the total amount of discharge for the storm event(s) sampled, the method of flow measurement, or estimation. Provide the data and duration of the storm event(s) sampled, rainfall measurements, or estimates of the storm event which generated the sampled runoff and the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event.

Part VII-E

List any toxic pollutant listed in Tables 2F-2, 2F-3, or 2F-4 which you currently use or manufacture as an intermediate or final product or byproduct. In addition, if you know or have reason to believe that 2,3,7,8-te-trachlorodibenzo-p-dioxin (TCDD) is discharged or if you use or manufacture 2,4,5-trichlorophenoxy acetic

acid (2,4,5,-T); 2-(2,4,5-trichlorophenoxy) propanoic acid (Silvex, 2,4,5,-TP); 2-(2,4,5-trichlorophenoxy) ethyl, 2,2-dichloropropionate (Erbon); O,O-dimethyl O-(2,4,5-trichlorophenyl) phosphorothioate (Ronnel); 2,4,5-trichlorophenol (TCP); or hexachlorophene (HCP); then list TCDD. The Director may waive or modify the requirement if you demonstrate that it would be unduly burdensome to identify each toxic pollutant and the Director has adequate information to issue your permit. You may not claim this information as confidential; however, you do not have to distinguish between use or production of the pollutants or list the amounts.

Item VIII

Self explanatory. The permitting authority may ask you to provide additional details after your application is received.

item X

The Clean Water Act provides for severe penalties for submitting false information on this application form.

Section 309(c)(4) of the Clean Water Act provides that "Any person who knowingly makes any false material statement, representation, or certification in any application, . . . shall upon conviction, be punished by a fine of not more than \$10,000 or by imprisonment for not more than 2 years, or by both. If a conviction of such person is for a violation committed after a first conviction of such person under this paragraph, punishment shall be by a fine of not more than \$20,000 per day of violation, or by imprisonment of not more than 4 years, or by both." 40 CFR Part 122.22 requires the certification to be signed as follows:

(A) For a corporation: by a responsible corporate official. For purposes of this section, a responsible corporate official means (i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy- or decision-making functions for the corporation, or (ii) the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25,000,000 (in second-quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

Note: EPA does not require specific assignments or delegation of authority to responsible corporate officers identified in 122.22(a)(1)(i). The Agency will presume that these responsible corporate officers have the requisite authority to sign permit applications unless the corporation has notified the Director to the contrary. Corporate procedures governing authority to sign permit applications may provide for assignment or delegation to applicable corporate position under 122.22(a)(1)(ii) rather than to specific individuals.

- (B) For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or
- (C) For a municipality, State, Federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes (i) the chief executive officer of the agency, or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., Regional Administrators of EPA).

Table 2F-1

Codes for Treatment Units

Physical Treatment Processes

1-A	Ammonia Stripping	1-M	Grit Removal
1-B	Dialysis	1-N	Microstraining
1-C	Diatomaceous Earth Filtration	1-0	Mixing
1-D	Distillation	1-P	Moving Bed Filters
1-E	Electrodialysis	1-Q	Multimedia Filtration
1-F	Evaporation	1-R	Rapid Sand Filtration
1-G	Flocculation	1-S	Reverse Osmosis (Hyperfiltration)
1-H	Flotation	1-T	Screening
1-1	Foam Fractionation	1-U	Sedimentation (Setting)
1-J	Freezing	1-V	Slow Sand Filtration
1-K	Gas-Phase Separation	1-W	Solvent Extraction
1-L	Grinding (Comminutors)	1-X	Sorption
	Chemica	Treatment Proc	cesses
2-A	Carbon Adsorption	2-G	Disinfection (Ozone)
2-B	Chemical Oxidation	2-H	Disinfection (Other)
2-C	Chemical Precipitation	2-1	Electrochemical Treatment
2-D	Coagulation	2-J	lon Exchange
2-E	Dechlorination	2-K	Neutralization
2-F	Disinfection (Chlorine)	2-L	Reduction
	Biologica	Treatment Proc	cesses
3-A	Activated Sludge	3-E	Pre-Aeration
3-B	Aerated Lagoons	3-F	Spray Irrigation/Land Application
3-C	Anaerobic Treatment	3-G	Stabilization Ponds
3-D	Nitrification-Denitrification	3-H	Trickling Filtration
	Otto	ther Processes	
4-A	Discharge to Surface Water	4-C	Reuse/Recycle of Treated Effluent
4-B	Ocean Discharge Through Outfall	4-D	Underground Injection
	_	ent and Disposa	• •
5-A	Aerobic Digestion	5-M	Heat Drying
5-B	Anaerobic Digestion	5-N	Heat Treatment
5-C	Belt Filtration	5-O	Incineration
5-D	Centrifugation	5-P	Land Application
5-E	Chemical Conditioning	5-Q	Landfill
5-F	Chlorine Treatment	5-R	Pressure Filtration
5-G	Composting	5-S	Pyrolysis
5-H	Drying Beds	5-T	Sludge Lagoons
5-1	Elutriation	5-U	Vacuum Filtration
5-J	Flotation Thickening	5-V	Vibration
5-K	Freezing	5-W	Wet Oxidation
5-L	Gravity Thickening	5	Cridation

Table 2F-2

Conventional and Nonconventional Pollutants

Bromide
Chlorine, Total Residual
Color
Fecal Coliform
Fluoride
Nitrate-Nitrite
Nitrogen, Total Organic
Oil and Grease
Phosphorus, Total
Radioactivity
Sulfate
Sulfite
Surfactants
Aluminum, Total
Barium, Total
Barium, Total
Cobalt, Total
Iron, Total
Magnesium, Total
Manganese, Total
Titanium, Total

Table 2F-3

Toxic Pollutants

Toxic Pollutants and Total Phenol

Antimony, Total Arsenic, Total Beryllium, Total Cadmium, Total Chromium, Total Copper, Total Lead, Total Mercury, Total Nickel, Total Selenium, Total

Dichlorobromomethane

1,1-Dichloroethane

1.2-Dichloroethane

1,1-Dichloroethylene

Silver, Total Thallium, Total Zinc, Total Cyanide, Total Phenols, Total

GC/MS Fraction Volatiles Compounds

Acrolein Acrylonitrile Benzene Bromoform

Carbon Tetrachloride Chlorobenzene

Chlorodibromomethane Chloroethane

2-Chloroethylvinyl Ether Chloroform

1,2-Dichloropropane 1,3-Dichloropropylene Ethylbenzene Methyl Bromide Methyl Chloride Methylene Chloride Tetrachloroethylene
Toluene
1,2-Trans-Dichloroethylene
1,1,1-Trichloroethane
1,1,2-Trichloroethane
Trichloroethylene
Vinyl Chloride

1,1,2,2,-Tetrachloroethane

Acid Compounds

2-Chlorophenol 2,4-Dichlorophenol 2,4-Dimethylphenol 4,6-Dinitro-O-Cresol 2,4-Dinitrophenol 2-Nitrophenol 4-Nitrophenol p-Chloro-M-Cresol Pentachlorophenol
Phenol
2,4,6-Trichlorophenol
2-methyl-4,6 dinitrophenol

Base/Neutral

Acenaphthene
Acenaphthylene
Anthracene
Benzidine
Benzo(a)a@thracene
Benzo(a)pyrene
3,4-Benzofluoranthene
Benzo(ghi)perylene
Benzo(k)fluoranthene
Bis(2-chloroethoxy)methane
Bis(2-chloroethyl)ether
Bis(2-chloroisopropyl)ether
Bis(2-chlylyhexyl)phthalate
4-Bromophenyl Phenyl Ether
Butylbenzyl Phthalate

2-Chloronaphthalene 4-Chlorophenyl Phenyl Ether Chrysene Dibenzo(a,h)anthracene 1,2-Dichlorobenzene 1,3-Dichlorobenzene 1,4-Dichlorobenzene 3,3'-Dichlorobenzidine Diethyl Phthalate Dimethyl Phthalate Di-N-Butyl Phthalate 2.4-Dinitrotoluene 2,6-Dinitrotoluene Di-N-Octylphthalate 1,2-Diphenylhydrazine (as Azobenzene)

Fluroranthene
Fluorene
Hexachlorobenzene
Hexachlorobutadiene
Hexachloroethane
Indeno(1,2,3-cd)pyrene
Isophorone
Napthalene
Nitrobenzene
N-Nitrosodimethylamine

N-Nitrosodimethylamine
N-Nitrosodi-N-Propylamine
N-Nitrosodiphenylamine
Phenanthrene
Pyrene
1,2,4-Trichlorobenzene

Pesticides

Aldrin
Alpha-BHC
Beta-BHC
Gamma-BHC
Delta-BHC
Chlordane
4,4'-DDT
4,4'-DDE
4,4'-DDD

Dieldrin
Alpha-Endosulfan
Beta-Endosulfan
Endosulfan Sulfate
Endrin
Endrin Aldehyde
Heptachlor
Heptachlor Epoxide
PCB-1242

PCB-1254 PCB-1221 PCB-1232 PCB-1248 PCB-1260 PCB-1016 Toxaphene

Table 2F-4 Hazardous Substances

Toxic Pollutant

Asbestos

Hazardous Substances

Acetaldehyde Allyl alcohol Allyl chloride Amyl acetate
Aniline
Benzonitrile
Benzyl chloride
Butyl acetate
Butylamine
Carbaryl
Carbofuran
Carbon disulfide
Chlorpyrifos
Coumaphos

Cresol Crotonaldehyde

Cyclohexane

2,4-D (2,4-Dichlorophenoxyacetic acid)
Diazinon
Dicamba
Dichlobenil
Dichlone
2,2-Dichloropropionic acid

Dichlorvos
Diethyl amine
Dimethyl amine

Dinitrobenzene
Diquat
Disulfoton
Diuron
Epichlorohydrin
Ethion
Ethylene diamine
Ethylene dibromide
Formaldehyde
Furfural
Guthion
Isoprene

Isopropanolamine

Kepone Malathion

Kelthane

Methoxychlor

Methyl mercaptan
Methyl methacrylate
Methyl parathion
Mevinphos
Mexacarbate

Monoethyl amine

Monomethyl amine

Mercaptodimethur

Naled

Napthenic acid
Nitrotoluene
Parathion
Phenolsulfonate
Phosgene
Propargite
Propylene oxide
Pyrethrins
Quinoline
Resorcinol
Stronthium
Strychnine
Styrene

2,4,5-T (2,4,5-Trichlorophenoxyacetic

acid)

TDE (Tetrachlorodiphenyl ethane) 2,4,5-TP [2-(2,4,5-Trichlorophenoxy)

propanoic acid]
Trichlorofan
Triethylamine

Trimethylamine Uranium Vanadium Vinyl acetate Xylene Xylenol Zirconium